

# User and installation manual



## VISION

**ENGLISH: PAGE 1**

**DEUTSCH: SEITE 31**

Current as of February 2024

All information contained in this manual is subject to change without prior notice.  
All rights reserved.

## Table of contents

1. Preface.....	4
2. Safety precautions.....	4
3. Assembly instructions.....	5
3.1. VISION Touch (53232, 53235).....	5
3.2. VISION table top units (53236, 53237, 53238).....	5
3.3. VISION connection terminal for kryographics (23664, 23665, 23666, 23667).....	5
3.4. cuplex kryos NEXT with VISION (21xxx).....	5
4. Electrical connections.....	5
4.1. VISION module connector overview.....	5
4.2. Connector "USB".....	5
4.3. Connector "aquabus".....	6
4.4. Connector "Flow/Alarm".....	6
4.5. Connector for temperature sensor.....	7
5. Operation.....	7
5.1. Configuration using USB connection.....	7
5.2. Operation via keys and display (VISION Touch only).....	7
5.3. Operation via aquaremote (devices with IR receiver only).....	8
6. aquasuite software.....	8
6.1. Installation of the aquasuite software.....	8
6.2. Basic operation.....	8
6.3. Symbols in the headlines.....	8
7. Overview pages (aquasuite).....	9
7.1. Desktop mode.....	9
7.2. Creating new overview pages and activating edit mode.....	9
7.3. Adding new elements.....	10
7.4. Editing existing elements.....	10
7.5. Values and names.....	10
7.6. Detailed data elements.....	10
7.7. Log data chart.....	11
7.8. User defined: Images, text, drawing elements.....	11
7.9. Export and import of overview pages.....	11
8. Data quick view and data log (aquasuite).....	12
8.1. Log settings.....	12
8.2. Analyze data.....	12
8.3. Manual data export.....	13
8.4. Automatic data export.....	14
9. Sensor configuration.....	14
9.1. Hardware temperature sensor.....	14
9.2. Hardware flow sensor.....	14

- 9.3. Software sensors (configuration using aquasuite only)..... 14
- 10. Display configuration..... 16
  - 10.1. General display settings..... 17
  - 10.2. Display screens..... 17
  - 10.3. Key assignment (VISION Touch only)..... 17
- 11. Infrared configuration (devices with IR receiver only)..... 17
  - 11.1. General settings IR receiver..... 17
  - 11.2. aquaremote multi device mode..... 18
  - 11.3. User defined infrared commands..... 18
  - 11.4. aquaremote: "VISION", "Computer", "Media" modes..... 18
  - 11.5. aquaremote: Special functions in "VISION" mode..... 19
  - 11.6. aquaremote: Special functions in "Computer" mode..... 19
  - 11.7. aquaremote: Special functions in "Media" mode..... 19
- 12. RGB configuration (devices with integrated RGB LED only)..... 19
  - 12.1. LED mode..... 19
  - 12.2. Color settings..... 20
  - 12.3. Sensor controlled mode..... 20
- 13. Time configuration..... 20
  - 13.1. Time zone, daylight saving time, time format..... 20
  - 13.2. Timer..... 20
  - 13.3. Alarm clock (devices with integrated RGB LED only)..... 20
- 14. Alarm configuration..... 20
  - 14.1. Alarm reporting and alarm limits..... 21
- 15. Profiles..... 21
  - 15.1. Manual profile selection..... 21
  - 15.2. Automatic profile selection..... 21
  - 15.3. Profile configuration..... 21
- 16. System settings VISION..... 21
  - 16.1. Device information..... 22
  - 16.2. Factory defaults..... 22
  - 16.3. aquabus configuration..... 22
  - 16.4. Flow/Alarm header function..... 22
  - 16.5. Note tool..... 22
  - 16.6. Standby behavior..... 23
  - 16.7. Firmware update and language selection (aquasuite only)..... 23
- 17. Playground (aquasuite)..... 23
  - 17.1. Input values..... 23
  - 17.2. Virtual Software Sensors..... 24
  - 17.3. Output actions..... 24
  - 17.4. Global profiles..... 25
  - 17.5. Hotkeys..... 25
- 18. aquasuite web..... 25

18.1. Data export.....	26
18.2. Data access.....	26
18.3. Data import.....	26
19. Basic settings (aquasuite).....	27
19.1. Language.....	27
19.2. Create overview pages.....	27
19.3. Reorder menu items.....	27
19.4. Units.....	27
19.5. Event log.....	27
19.6. Application start-up.....	27
19.7. Service administration.....	27
19.8. Audio and video.....	28
19.9. Updates and update service.....	28
19.10. E-mail and MQTT accounts.....	29
20. Technical details and care instructions.....	29
20.1. Technical details.....	29
20.2. Care instructions.....	29
20.3. Waste disposal.....	30
20.4. Contact Aqua Computer.....	30

## 1. Preface

The VISION module is a multi-purpose display and monitoring controller with integrated OLED display.

As this manual covers all members of the VISION series, some chapters of this manual will not apply to all product versions.

Considering the fast technical development, we reserve the right to perform alterations to the products at any time. It therefore is possible that your product does not correspond precisely to the descriptions or especially the illustrations in this manual.

## 2. Safety precautions

The following safety precautions have to be observed at all times:

- Read this manual thoroughly and entirely!
- Save your data onto suitable media before working on your hardware!
- This product is not designed for use in life support appliances, devices, or systems where malfunction of this product can reasonably be expected to result in personal injury. Aqua Computer GmbH & Co. KG customers using or selling this product for use in such application do so at their own risk and agree to fully indemnify Aqua Computer GmbH & Co. KG for any damages resulting from such application!

### 3. Assembly instructions

#### 3.1. VISION Touch (53232, 53235)

This device can either be placed on a flat surface by attaching the supplied clip-on stand or be mounted using a cable tie.

#### 3.2. VISION table top units (53236, 53237, 53238)

Place the device on a flat surface.

#### 3.3. VISION connection terminal for kryographics (23664, 23665, 23666, 23667)


The connection terminal ships with a separate installation manual. Install the terminal according to this manual.

#### 3.4. cuplex kryos NEXT with VISION (21xxx)

The cuplex kryos NEXT ships with a separate installation manual. Install the water block according to this manual.

### 4. Electrical connections

#### 4.1. VISION module connector overview




ATTENTION: Completely turn off your power supply or disconnect the mains power cord from the wall outlet before connecting or disconnecting any cables to/from the device!

#### 4.2. Connector “USB”

This connector is used for USB communication with a PC. Connect to an internal USB header of your motherboard. Take special care to make sure the pin alignment matches your motherboard!

Pin assignment: Pin 1 not connected  
 Pin 2 GND (black)  
 Pin 3 D+ (green)  
 Pin 4 D- (white)  
 Pin 5 +5 V (red)

The corresponding connector on the motherboard is usually a 9 pin connector with two independent USB ports. Both rows of 4/5 pins can be used to connect an USB device. The black wires (GND) are to be connected to the side of the missing pin, see picture with colored pin assignment.



### 4.3. Connector “aquabus”

Connector for communication with other Aqua Computer devices. USB and aquabus interface can be used at the same time.

Pin assignment: Pin 1 GND  
 Pin 2 aquabus SDA  
 Pin 3 aquabus SCL  
 Pin 4 +5 V

Compatible aquabus devices:

- aquaero 6 XT (53146, 53206, 53250, 53251, 53262, 53263)
- aquaero 6 PRO (53145, 53253)
- aquaero 6 LT (53234)
- aquaero 5 XT (53089, 53125, 53249)
- aquaero 5 PRO (53090, 53252)
- aquaero 5 LT (53095)

### 4.4. Connector “Flow/Alarm”

Alternative configurations: Depending on configuration, this connector can either be used as a flow sensor input or as an alarm output. It is not possible to use both functions simultaneously!

Please refer to chapter 16.4. for connector configuration.

#### Utilization as flow sensor input

Flow sensor and special interconnecting cable are optional accessories and not included in delivery.

Pin assignment: Pin 1 GND  
 Pin 2 flow sensor +5 V  
 Pin 3 flow sensor signal

Compatible flow sensors:

- Flow sensor with 5.6 mm nozzle (53061, requires cable 53212)
- Flow sensor “high flow” (53068, requires cable 53212)
- Flow sensor high flow LT (53291)
- Flow sensor high flow 2 (53292)

### Utilization as alarm output

The alarm output can be connected to the power switch header of the motherboard using an additional specialized cable (53216, not included in delivery).

Depending on the VISION module version, the output may be controlled by alarm configuration, timer function, touch key or infrared command.

Pin assignment: Pin 1: GND

Pin 2: do not connect!

Pin 3: open drain max 3.3 V / 5 mA

## 4.5. Connector for temperature sensor

Connector for a temperature sensor. Some VISION series products feature an integrated temperature sensor connected to the VISION module, in this case no additional sensor can be connected!

Compatible sensors:

- Temperature sensor inline G1/4 for VISION (53218)
- Temperature sensor inner/outer thread G1/4 for VISION (53219)
- Temperature sensor G1/4 for VISION (53220)
- Temperature sensor 70 cm for VISION (art. 53211)
- Temperature sensor 5 cm for VISION (art. 53227)

## 5. Operation

### 5.1. Configuration using USB connection

The VISION module can be connected to a PC via USB interface and can then be configured using the aquasuite software. Comprehensive visualization and logging options are also available in the aquasuite software. However, an USB connection is not required for operation if the vision module is fully configured and connected to an aquaero 5/6 device via aquabus connection.

### 5.2. Operation via keys and display (VISION Touch only)

Devices of the VISION Touch series are equipped with four keys that can be used to configure the device. Alternatively, individual key functions may be assigned for each display screen.

In factory default configuration, the ◀ ▶ keys will select information pages during display mode. The ▲ ▼ keys will open the device menu while in display mode.

During configuration via keys and display, the aquasuite software should be closed on a connected PC! Otherwise, the aquasuite will overwrite and thereby cancel any settings made at the device itself.

### 5.3. Operation via aquaremote (devices with IR receiver only)

The configuration menu of devices with IR receiver can also be accessed using an aquaremote (53088, not included in delivery). Please see chapter 11. for details on IR receiver configuration and key assignments.

## 6. aquasuite software

The Windows software aquasuite is an extensive software suite and can be used for configuration and monitoring. The software is not required for operation though. All configuration parameters can be saved into the device's memory.

Please note: Depending on the type of product you are using, some features may not be available for your device.

### 6.1. Installation of the aquasuite software

For configuration and monitoring of our products with USB interface, the aquasuite software is available for download from our website [www.aqua-computer.de](http://www.aqua-computer.de). You will find the setup program in the support section of the website under Downloads/Software.

The setup program checks all connected USB devices for embedded update service periods and offers various aquasuite versions depending on detected devices. If no device with update service for the latest aquasuite version is found, a warning is displayed and older aquasuite versions that do not require an update service purchase can be selected for installation. For installation and update service validation, an internet connection is required.

The latest aquasuite version may also be installed if no suitable update service period has been found in a device. Subsequently, update service may be purchased or an existing key may be entered within the aquasuite. These functions can be accessed in the aquasuite/Updates tab.

### 6.2. Basic operation

The program window is divided into two main areas. On the left side, a list of "overview pages", data quick view, data logger, device pages, aquasuite web and aquasuite configuration is displayed, the right side shows the details of the currently selected list element. The list can be hidden or restored by clicking the arrow symbol in the upper left corner.

List elements may be minimized or maximized for easier access by clicking the title bar. The title bars may contain various symbols that will be explained in the following chapter.

### 6.3. Symbols in the headlines






Click the plus symbol in the “Overview pages” headline to create a new overview page.



Clicking the monitor symbol will toggle desktop mode for this overview page. While desktop mode is active, the color of the symbol will change to orange.



Overview page: Clicking the padlock symbol will unlock or lock this overview page for editing. Device: Device can not be used due to update service problems, see “Updates and update service” for details.



Clicking the gear symbol will access the basic configuration page of the selected list element.



In order to save all settings into a device, click the disk symbol in the headline.



This symbol indicates that communication with this device is not possible at the moment. Check USB connection and power supply of the device if necessary.

## 7. Overview pages (aquasuite)

Current sensor readings and diagrams from all supported devices can be displayed in overview pages. For each device a pre-configured overview page is automatically generated the first time the device is connected to the PC. These pages can be individually modified and new pages can be created. Within one overview page, data from all connected devices can be accessed.

### 7.1. Desktop mode

Each overview page can be displayed directly on your desktop. You can enable desktop mode for an overview page by clicking the monitor symbol in the list of overview pages. Desktop mode can only be enabled for one overview page at a time. With desktop mode enabled, elements of the overview page may cover program symbols on your desktop, but mouse clicks are transmitted to underlying desktop symbols.

If a overview page is unlocked for editing while desktop mode is active, the page will be displayed in the aquasuite window for editing and the current desktop will be displayed as background for your convenience.

### 7.2. Creating new overview pages and activating edit mode

In order to create a new overview page, click the plus symbol in the headline “Overview pages”.

Existing overview pages can be unlocked for editing by clicking lock symbol in the page listing.

### 7.3. Adding new elements


If the currently selected overview page is unlocked for editing, a plus symbol is displayed in the top right corner of the screen. Click the symbol to add a new element to the page and select the desired element from the following list. All available data is displayed in a tree diagram, click the arrow symbols to access individual items.

Confirm your selection by clicking the check symbol in the bottom right corner. The new element will be displayed in the upper left corner and the configuration window is displayed. Configure the element as described in the next chapters.

### 7.4. Editing existing elements

If the currently selected overview page is unlocked for editing, right-clicking an element will access a context menu.

To access the settings of an element, select "Settings" in the context menu or simply double click the element. If you want to move an element, "drag" this element while holding down the mouse button. Release the mouse button when the element is at the desired position.



### 7.5. Values and names

If the currently selected overview page is unlocked for editing, right-click an element and select "Settings". You may also double click the element.

Font face, size and color as well as position, decimal places and unit can be configured for individual values.

### 7.6. Detailed data elements

If the currently selected overview page is unlocked for editing, right-click an element and select "Settings". You may also double click the element. Apart from position, size and color, the style of the element can be selected and configured. The following styles are available:

- **Headline only:** Compact display as a headline.
- **Text:** Displays the numerical value in a box with a headline.
- **Bar graph:** Displays numerical value as well as bar graph.
- **Chart:** Displays the value in chronological sequence as a chart.
- **Gauge:** Displays the value as an analog gauge.

All display styles offer extensive configuration options, additionally statistical data such as minimum, maximum and average can be displayed.

## 7.7. Log data chart

This element can be used to display charts on overview pages. The charts have to be created using the data log functionality of the aquasuite before they become available for overview pages. Please refer to the next chapter for details. Once a chart has been configured, it can be selected from the “Chart selection” list on the “Display” tab of the settings dialog.

## 7.8. User defined: Images, text, drawing elements

By using user defined controls, simple drawing elements such as circles, rectangles and texts as well as images and more sophisticated elements can be added to an overview page. To do so, add an “User defined” element to an overview page. Switch to the “Display” tab in following dialog box, select the type of element to be created from the drop down menu and confirm your selection by clicking the “Load preset” button. Depending on the type of element, an additional dialog may appear before the code (XAML, Extensible Application Markup Language) of the new element is displayed in the lower part of the dialog window. You may want to customize the code. By clicking the “Ok” Button, the new control is saved to the overview page.

Step-by-step example to add an image: Select “Image” from the drop down menu and click the “Load preset” button. Select an image file using the following file selection dialog. The code is then displayed in the lower part of the dialog window and can be modified. Save the new control by clicking the “Ok” button. The picture will be displayed on the overview page.

More complex controls such as data bindings and animations are also available but will require some programming experience for configuration.

## 7.9. Export and import of overview pages

Elements and complete overview pages can be exported from the aquasuite and can then be imported either on the same PC or on other PCs. For export as well as import, the overview page must be in edit mode.

To export a complete page, right click a free spot of the page and select “Export page” from the context menu. To export individual elements, select the element or elements, perform a right click and select “Export selected” from the context menu. For import, right click a free spot of the page and select “Import page” or “Import items” from the context menu. Using “Import page”, the current page will be deleted and only the imported page items will be displayed, using “Import items” will add the items from file to the current page without altering the existing items. During import, the elements will be assigned to devices using the following scheme:

If a device with identical serial number is found on the computer, no changes are made.

If no device with identical serial number is found on the computer, the element will be assigned to the first device found of identical type.


When importing complex pages with elements referring to more than one device, it is recommended to edit the device assignment in the file using a text editor prior to importing.

## 8. Data quick view and data log (aquasuite)

All data currently monitored by the aquasuite can be accessed in the “Data quick view” section. This includes data from connected USB devices as well as hardware data supplied by the Aqua Computer background service. Displayed data may be filtered using the text box next to the magnifier icon, a chart shows the development over a maximum of ten minutes. All data shown here is not stored permanently.

In contrast, the “Data log” may be used to selectively and permanently store data from all connected Aqua Computer devices and hardware data supplied by the background service. Logged data can then be analyzed by creating charts or be exported to files. Data is only logged while the aquasuite software is being executed.

### 8.1. Log settings



The log settings can be accessed by clicking the “Log settings” element below the “Data log” headline in the listing. To log data, create a new log data set by clicking the plus symbol in the upper right corner of the settings window. Enter name, time interval and configure automatic deletion of old data to meet your requirements. You may then add the data sources to log by clicking the plus symbol in the “Data sources” window section. You may add an unlimited number of data sources to each log data set, the total number of log data sets is also unlimited.

### 8.2. Analyze data



Logged data can be visually evaluated as charts. To do so, select “Analyze data” below the “Data log” headline in the listing. The chart will initially be empty, directly below the chart are eight buttons to modify the chart. In the lower section of the window, the chart data can be configured.


To add data to the chart, first select the “Data sources” tab in the chart configuration and select a data set to be displayed. If no data sources are available, you will have to configure the log settings as described in the chapter “Log settings” of this manual. Select the time period to be displayed on the right side of the window and add the data to the chart by clicking the “Add data to chart” button. Repeat this procedure if you want to display more than one data set in the chart.

You may modify the chart using the “Chart setup” and “Data series setup” tabs. Finally, you can use the “Chart manager” tab to save the current chart configuration and to load or delete previously saved configurations. All saved chart configurations will be available on overview pages for the “Log data chart” element.


The currently displayed chart can be edited by using the buttons directly below the chart and may also be saved as an image file. The button corresponding to the currently selected function is highlighted by an orange frame. Please refer to the following list for details on each function:



To save the currently displayed chart as an image file, click the floppy disk symbol and select a name and location in the following dialog.



This function can be used to add horizontal lines to the chart. While this function is activated, simply click into the chart to add a line at the current cursor position.




This function can be used to add vertical lines to the chart. While this function is activated, simply click into the chart to add a line at the current cursor position.



This function can be used to add annotations to the chart. While this function is activated, simply click into the chart to add an annotation at the current cursor position. By clicking into the text box, you may edit the text. You may also drag the little circle beside the text box to move the connecting line to the desired position. Use drag and drop to move existing annotations.




This function can be used to remove horizontal/vertical lines or annotations from the chart. While this function is activated, simply click the element to be removed.



This function can be used to move the visible portion of the chart. Press and hold the mouse button while moving the cursor in the chart to select the position to be displayed, then release the button.



This function can be used to zoom in and out. Use the mouse wheel or select the area to be displayed. You can reset the zoom settings by double-clicking in the chart area.



This function can be used to reload and update the chart.




This function will completely remove the chart.

### 8.3. Manual data export

Saved data can be exported from the data log into a XML file. To do so, select "Analyze data" below the "Data log" headline in the listing. Select the "Data sources" tab in the chart configuration and select a data set to be exported. If no data sources are available, you will have to configure the log settings as described in the chapter "Log settings" of this manual. Select the time period to be exported on the right side of the window and start the export process by clicking the "Export data" button. Enter a file name and path in the following dialog window.

## 8.4. Automatic data export



The automatic data export feature can be used to save data from the aquasuite into an XML file on the hard disk or in the RAM (“memory mapped file”) in a regular time interval. The automatic data export will always overwrite the previously saved data, so the file always contains only the most recent data set. Select “Automatic data export” below the “Data log” headline in the listing to access the settings screen. Create a new export data set by clicking the plus symbol in the upper right corner of the screen. Enter name, path and time interval to meet your requirements. You may then add the data sources to log by clicking the plus symbol in the “Data sources” window section. You may add an unlimited number of data sources to each export data set, the total number of export data sets is also unlimited.

## 9. Sensor configuration



aquasuite: Select “Sensors” from the device list below the “VISION” entry. In the upper area, the eighteen available sensors are displayed including current data. In the lower area, the currently selected sensor can be configured.

Device menu: Select “Sensors” from the menu list and confirm by pressing the right arrow key.

### 9.1. Hardware temperature sensor

The first sensor in the list represents the temperature sensor input of the VISION module. The temperature can be displayed either in degree Celsius or Fahrenheit. The log interval determines the time difference between sensor data continuously stored in memory and thereby the time period displayed in charts.

If necessary, each temperature sensor can be calibrated by adding an offset of  $\pm 15$  °C/°F.

### 9.2. Hardware flow sensor

The second sensor in the list represents the flow sensor input of the VISION module. Calibration values for sensors sold by Aqua Computer can conveniently be selected from a drop-down list. Select the appropriate entry for the flow sensor connected to the VISION module.

If necessary, the flow rate can be calibrated by  $\pm 10$  %.

### 9.3. Software sensors (configuration using aquasuite only)

The last sixteen sensors in the list are software sensors and can be used to transmit sensor data that is not physically available to the VISION module from the computer by USB connection or from an aquaero 5/6 by aquabus connection.


For each software sensor, the interface (USB or aquabus) used to receive data can be selected. The log interval determines the amount of time between any two sensor readings continually stored in device memory and thereby the total time interval displayed in graphical charts. Select the appropriate unit for each configured data source as well. For manipulation of the displayed sensor value, a scale factor and an offset may be configured. Data from third party software regularly requires the scale factor to be adjusted.

### Transmission of sensor data via USB interface


During installation of the aquasuite, the background service “Aqua Computer Service” is also installed. This service supplies various data from PC components and imported data from aquasuite web, additionally sensor data provided by third party software can be accessed. In order to access third party software data, the third party software has to be correctly installed, configured and running.

Currently, the “Aqua Computer Service” supports data transfer from “HWiNFO” (REALiX, Freeware, [www.hwinfo.com](http://www.hwinfo.com)) and “AIDA64” (FinalWire Ltd., subject to license fees, [www.aida64.com](http://www.aida64.com)).

In the HWiNFO settings menu, “Shared Memory Support” must be activated and the “Sensor Status” window has to be open:



In the AIDA64 preferences menu, “Enable shared memory” must be activated in the “External Applications” sub-menu:



By clicking the plus symbol labeled “Data source”, one of the provided sensors can be assigned to the selected software sensor.

### Transmission of sensor data via aquabus interface

Sensor data to be transmitted via aquabus is determined solely by the connected aquaero 5/6 controller. For configuration, the aquaero has to be connected to the PC (at least temporarily) via USB.

Select “aquabus” from the device list below the “aquaero” entry. From the “Currently connected aquabus devices” section, select the appropriate VISION module to receive sensor data. Up to four sensors can be selected to be transmitted to the VISION module as well as the sensor number to be used.

## 10. Display configuration



aquasuite: Select “Display” from the device list below the “VISION” entry. In the upper area, the twelve configurable display screens are displayed. In the lower area, the selected screen can be configured.

Device menu: Select “Display” from the menu list and confirm by pressing the right arrow key.



### 10.1. General display settings

Display brightness and automatic change of the displayed screen can be configured.

As with all OLED displays, the brightness of active pixels will reduce over time. For a homogeneous wear of all pixels, the display can automatically be inverted half of the time. In order to counteract existing wear, the inverted mode can be permanently activated.

### 10.2. Display screens

For display mode, twelve configurable screens are available. For each screen, one of the versatile template can be selected and configured. Depending on the template, data sources, texts and images can be configured.

For the audio display pages, audio analysis must be activated and configured in the aquasuite, see chapter 19.8.

### 10.3. Key assignment (VISION Touch only)

For each screen, all four keys can be assigned individually.

In particular, it is possible to configure a screen that is only displayed during standby and configure an USB keyboard command to wake up the PC when a key of the VISION module is pressed. To do so, assign "User defined 12" to the key, click the "Edit" button and select "Power (system)" for this key. In a similar fashion, you could use the up and down keys to adjust PC volume when the media player screen is displayed. The template with four images can be used to assign individual functions to each key and label them with custom made symbols – let your creativity run wild.

## 11. Infrared configuration (devices with IR receiver only)



aquasuite: Select "Infrared" from the device list below the "VISION" entry.

Device menu: Select "Infrared" from the menu list and confirm by pressing the right arrow key.

### 11.1. General settings IR receiver

The infrared receiver of the VISION module can be disabled completely.

If activated, processing of infrared codes sent by an aquaremote (53088, not included in delivery) can be enabled and PC mouse and PC keyboard functionality of the aquaremote may be configured. Keyboard events forwarded to the PC will be processed by the PC according to the currently selected keyboard layout in the operating system. The aquaero supports two different keyboard layouts for QWERTY and QWERTZ layouts.

The “IR priority” setting defines the default mode of operation of the aquaremote. After approximately 10 seconds without IR activity, the mode is reset to the selected mode.

## 11.2. aquaremote multi device mode

The multi device mode can be used to control up to ten VISION modules independently using an aquaremote. Configure a unique key for each VISION module. In order to control a specific VISION module with activated multi device mode, press the desired mode key (🏠, 📺 or TV) followed by the configured unique key. The selected VISION module will process all following infrared commands of the aquaremote. After approximately 10 seconds without IR activity, the VISION module automatically disables processing of IR commands again.

## 11.3. User defined infrared commands

The VISION module can execute up to ten user defined actions after receiving a specific infrared code. The the actions can be triggered by pressing the “ASD-FGHJKL←” keys of the aquaremote, additionally an infrared code from a multitude of commercially available remote controls can be assigned to each action. VISION specific functions as well as USB keyboard commands including media and system keys may be assigned as actions.

## 11.4. aquaremote: “VISION”, “Computer”, “Media” modes

Processing of infrared commands received by the VISION module depends on current mode of operation. Key assignment differs in the three modes of operation. In “VISION” mode, all keys will be processed by the VISION module and not forwarded to the PC. In “Computer” and “Media” mode, all keys will directly be forwarded to the PC and not be processed by the VISION module.



Three keys of the aquaremote select the mode of operation: “VISION” mode is selected by pressing the “🏠” key, the “📺” key selects “Computer” mode and “Media” mode can be selected by pressing the “TV” key. The currently selected mode is displayed on the VISION module display for approximately two seconds after switching modes. The circular mouse control pad

and button are forwarded to the PC in all modes.

In “Computer” mode, the “↑” key toggles between lower and upper case characters and the “Alt” (green) and “Alt” (blue) keys activate and deactivate the numbers and special characters printed in the corresponding colors.

### 11.5. aquaremote: Special functions in "VISION" mode



- Exit menu
- One menu level up
- Previous
- Next
- Enter menu/confirm
- No function

During display mode, the keys "QWERTYUIOP" correspond to the configured information pages ("Q" first page, "W" second page, ...).  
The keys "ASDFGHJKL←" can be assigned to commands.

### 11.6. aquaremote: Special functions in "Computer" mode



- No function
- Context menu
- Cursor keys
- Enter
- Page up/down

### 11.7. aquaremote: Special functions in "Media" mode



- Menu navigation back
- Menu
- Next/previous track
- Menu navigation up/down
- Play/Pause
- Menu +/-
- Volume up/down/mute

## 12. RGB configuration (devices with integrated RGB LED only)



aquasuite: Select "RGB" from the device list below the "VISION" entry.

### 12.1. LED mode

The RGB illumination can either be controlled by a sensor input or be set to a fixed color or a color gradient.

## 12.2. Color settings

Depending on the current mode, one or two colors can be defined. Colors can conveniently be set using the graphical color and brightness selectors, alternatively corresponding values can be set manually.

## 12.3. Sensor controlled mode

In Sensor controlled mode, two colors can be defined corresponding to two sensor readings (for instance temperatures). The VISION module generates a color gradient for sensor values between these limits.

# 13. Time configuration



aquasuite: Select "Time settings" from the device list below the "VISION" entry.

Device menu: Select "System" from the menu list and confirm by pressing the right arrow key. Proceed to select the "Time" menu entry.

## 13.1. Time zone, daylight saving time, time format

Adjust the time zone setting to reflect the deviation of the local time from UTC in hours. You may also choose to use automatic daylight saving time adjustment and your preferred time format.

## 13.2. Timer

The VISION module can be used as a countdown timer. Actions may be triggered when the timer is started or runs out.

Devices with integrated RGB LED only: The RGB LED can be configured to visualize the current timer state. If activated, the LED will be white for the first 50 % of the timer interval, followed by blue for another 25 % and green for the final 25 %. The LED will then blink red for 15 seconds after the timer has run out before returning to normal operation.

## 13.3. Alarm clock (devices with integrated RGB LED only)

The VISION module can be used as an optical alarm clock. Time, days, colors and duration can be configured. Please note that the VISION module does not contain a buffered real time clock, so the clock is reset if power supply to the device is interrupted.

# 14. Alarm configuration

aquasuite: Select "Alarms" from the device list below the "VISION" entry.



Device menu: Select “Alarms” from the menu list and confirm by pressing the right arrow key.

### 14.1. Alarm reporting and alarm limits

Select the data sources to be monitored and set appropriate alarm limits. If the current reading is below the limit (flow sensors) or higher than the limit (temperature sensors), an alarm will be raised if the check box “Activate alarm evaluation” is set for this value.

While an alarm condition is detected, the device display will permanently show a corresponding information screen. If more than one alarm is active, the displayed information will alternate between corresponding screens in short order.

On the alarm page within the aquasuite, all sources that currently raise an alarm are highlighted with a red background color. Alarms that have been active at least once since device start-up, but are not active presently, are highlighted with a yellow background color.

Make sure only to use readings for alarm evaluation that are functional with your specific setup.

## 15. Profiles



aquasuite: Select “Profiles” from the device list below the “VISION” entry. The profile management can be used to save four configurations as profiles and activate them manually or automatically. Profile management is a software feature of the aquasuite and requires a USB connection to the VISION module.

### 15.1. Manual profile selection

Select the profile to be activated by clicking the corresponding button.

### 15.2. Automatic profile selection


Profiles can be activated automatically using the global profiles feature of the aquasuite, see chapter 17.4. for details.

### 15.3. Profile configuration

All configuration changes are automatically stored in the currently active profile. The current configuration can also be stored in any other profile by clicking the corresponding button.

## 16. System settings VISION

aquasuite: Select “System” from the device list below the “VISION” entry.



Device menu: Select “System” from the menu list and confirm by pressing the right arrow key.

### 16.1. Device information

The details displayed here might be required when you contact our service for support. You may enter a “Device description” for easier identification, this text will be displayed in the device list and in the data quick view.

### 16.2. Factory defaults

Click the button “Reset device to factory defaults” in the aquasuite or select the “Factory defaults” entry from the menu for a complete reset of all settings. You will have to completely reconfigure the device after resetting it to factory defaults!

### 16.3. aquabus configuration

Before connecting multiple VISION modules simultaneously to an aquaero 5/6 via aquabus, each device has to be configured to a unique aquabus address. If only one device is connected via aquabus, this step may be skipped. Addresses 22, 23, 24 and 25 are available.

Changes to the bus address configuration are effective within a few seconds. However, it may take up to five minutes for a connected aquaero to update its configuration.

### 16.4. Flow/Alarm header function

The “Flow/Alarm” header of the VISION module can either be used as a flow sensor input or as an alarm output:

- Flow sensor: You may connect a flow sensor to this header using the appropriate connection cable (not included in delivery).
- Power switch (53216): This mode can be used for emergency shutdown of the PC, if the “RPM” header is connected to the power switch header of the motherboard using a suitable cable (art. 53216). Before connecting the cable, make sure the pump is configured correctly! After connecting the cable, test the setup by deliberately creating an alarm condition. If the PC is not shut down, the cable header connected to the motherboard must be rotated by 180 degrees and the test has to be repeated. Emergency shutdown may result in data loss as operating system and running programs are not shut down properly!

### 16.5. Note tool

The note tool can be used to display up to five lines of user defined text on the VISION module display. Please make sure to use the corresponding display template for one of the twelve configurable screens of the VISION module.

## 16.6. Standby behavior

The standby settings determine, for which USB- or aquabus conditions the VISION module will enter standby mode. Depending upon configuration, different display screens will be display during standby mode. Alarm evaluation can be disabled for standby mode.

## 16.7. Firmware update and language selection (aquasuite only)

The most up to date firmware for all supported devices is always included in the current version of the aquasuite software. The button “ Update firmware now” will start the update process for the device firmware.

During the firmware update process, the language of the VISION module device menu will automatically be set to the currently selected language in the aquasuite software. To change the language of the VISION module menu, first select the desired language in the basic aquasuite settings and restart the aquasuite software. Afterwards, perform a firmware update of the VISION module to change the language.

During the firmware update process, do not disconnect the device from the PC and do not power down the PC! After the firmware is successfully updated, the aquasuite software will be automatically closed.

# 17. Playground (aquasuite)

Click the entry “Playground” to configure Virtual Software Sensors, global profile management and hotkeys.

## 17.1. Input values



Input values defined in this section can be manipulated by individually configured control elements, for example sliders or buttons.

Create a new input value by clicking the plus symbol in the upper right corner of the “Input values” window and configure the properties as desired. A name, an icon, a unit, a range of values as well as a initial value can be assigned to each input value. This new input value will then be available to be displayed on overview pages and in the quick view section and can be used as a data source for software sensors and virtual software sensors.

In the lower area of the window, control elements can be created and configured to manipulate the input value. These preconfigured control elements can then be used for overview pages or in the system tray.

## 17.2. Virtual Software Sensors




Virtual Software Sensors can be used for extensive yet easy to use adaptation and calculation of sensor values using mathematical and logical functions as well as filters.

Create a new Virtual Software Sensor by clicking the plus symbol in the upper right corner of the “Virtual Software Sensors” window. Each Virtual Software Sensor always has an “Out” element which will provide the resulting sensor value. In the settings dialog of this element, the name and unit of the sensor can be configured. You can now add data sources and function blocks to the lower area of the sensor window and connect inputs and outputs of the blocks with lines. Connect the output of the last function block with the “Out” element.


The resulting virtual sensor can be used within the aquasuite software, for example for overview pages, additionally it may be transmitted via USB connection to connected devices that feature software sensors.

The following (very simple) example calculates the average out of two temperatures:



Virtual software sensors are updated once per second and re-calculated with the numbers valid in that particular moment. When using fast changing input values, extreme values can therefore either be used or ignored for the calculation. No smoothing or averaging is taking place.

## 17.3. Output actions



While the virtual software sensors are used as a value within the aquasuite, output actions configured in this section are used to trigger events. Various notification events including emails and MQTT messages are available. Additionally, external programs can be started.

Create a new output action by clicking the plus symbol in the upper right corner of the “Output actions” window and configure the properties as desired. Each output action always has an “Output” element which represents the event itself. In the settings dialog of this element, the event to be executed can be selected and configured.

You can now add data sources and function blocks to the lower area of the window and connect inputs and outputs of the blocks with lines. Connect the output of the last function block with the “Output” element. The event will be executed when the input of the “Output” element reaches a value greater than zero.



Output actions are updated once per second and re-calculated with the numbers valid in that particular moment. When using fast changing input values, extreme values can therefore either be used or ignored for the calculation. No smoothing or averaging is taking place. Example: If thresholds are exceeded for very short periods of time lasting less than one second, the action can be executed or not be executed seemingly at random, depending on whether the thresholds is exceeded in the exact moment the calculation is performed.

## 17.4. Global profiles



The global profile management can be used to conveniently change settings in multiple devices simultaneously and activate desktop pages. Individual actions can be defined for each of the four profiles, switching between profiles can either be done manually or automatically depending on configurable rules.

In order to use this feature, set up profiles within the individual device configurations first. These profiles can then be activated using the global profile management. Not every type of device supports profiles.

Buttons in the upper window area can be used to switch between global profiles. Alternatively, the profile icon in the title bar of the aquasuite window or a profile icon in the system tray may be used.

Example use cases: Switching of LED illumination settings depending on current time of day or modification of fan settings when a graphics application is launched.

Notice for profile activation depending on running applications: During configuration of the respective rule in the aquasuite, the application to be configured must already be running. The application selection within the aquasuite will always show currently running applications and processes only.

## 17.5. Hotkeys



Hotkeys are key combinations that will be processed system-wide and can activate global profiles or desktop pages. The configured key combinations will be registered in the operating system and be processed by the background service. If the configured actions only use the profile management, the aquasuite does not have to be running for hotkeys to be operational; if desktop pages are used, the aquasuite must be running.

Do not use key combinations for this function that are required by other applications.

## 18. aquasuite web

Click the entry "aquasuite web" to publish data on the internet or import data from the internet. The server for this service is operated by Aqua Computer and provided for use with the aquasuite, without warranty for error free operation or perma-

ment availability. Aqua Computer reserves the right to limit or cancel this service at any time.

### 18.1. Data export



To publish data, create a new export data set by clicking the plus symbol in the upper right corner of the “Data export” window. The name of the data set may be modified to meet your requirements. You may then add the data sources to export by clicking the plus symbol in the “Data sources” window section. By clicking the gear symbol, the name of the corresponding value can be changed. Up to 30 data sources can be added to each export data set, the total number of export data sets is limited to 10. All selected values will be transmitted to the Aqua Computer server by the Aqua Computer background service approximately every 15 seconds, even after closing the aquasuite.

Notice regarding data security: All data contained in the configured export data sets is transmitted to the Aqua Computer server with transport security. The server stores the data set in volatile memory until a new data set is received or until 10 minutes have passed. Data received is not permanently stored, data is also not correlated to IP addresses or other personal data. Data on the server may be accessed by anyone without restrictions, furthermore automatic data collection and recording through third parties is possible. Use the data export feature for data that you want to publish publicly and are allowed to do so only.

### 18.2. Data access



Published data can be obtained from the Aqua Computer server in various formats. Generally, the “access key” is required to access data.

In addition to access through any internet browser and importing data into the aquasuite, data is also available in JSON format and compatible to Circonus. Furthermore, the server generates banner images in two different sizes from the transmitted data, suitable to be included in forums signatures. The code required for the Aqua Computer forums is provided for your convenience.

### 18.3. Data import




To import a data set from the Aqua Computer server, the “access key” of the data set is required. The access key can be found in the aquasuite on the computer providing the data in the “Data access” section.

Create a new import entry by clicking the plus symbol in the upper right corner of the “Data import” window. Enter the access key of the data set to be imported. Up to 10 data sets (each containing up to 30 values) can be configured.

In order to verify that data is being imported, use the “Data quick view” feature in the aquasuite. Navigate to “Data from Aqua Computer service”, then “aquasuite web”. For each imported data set, you should find an entry with the name of the

data set containing the individual values. It may take a few seconds before imported data is displayed.

## 19. Basic settings (aquasuite)



Click the entry "Settings" below the headline "aquasuite" to access basic settings for language, units and start-up of the software.

### 19.1. Language

Select a language from the drop down menu. After changing the language setting, the software will have to be restarted.

### 19.2. Create overview pages

After activating the "Generate device overview pages", new overview pages with default settings will be created for all devices.

### 19.3. Reorder menu items

The order in which overview pages and devices are displayed in the list can be adjusted to your preference. Activate the reorder mode by clicking the "Edit menu order" button or by clicking and holding one of the elements for a few seconds. Sort the list items by clicking the arrow symbols and exit the reorder mode by clicking the check symbol on the right side of the window when done.

### 19.4. Units

Select the units to be used for temperature and flow values from the drop down menus. After changing these settings, the software will have to be restarted.

### 19.5. Event log

Events from various parts of the aquasuite can be saved to text files. Use the buttons to view the files either internally in the aquasuite or with an external program.

### 19.6. Application start-up

You may customize start-up behavior to suit your preferences. You may also select to hide the task bar symbol of the software when minimized.

### 19.7. Service administration



The background service configures special USB settings for all connected Aqua Computer devices, provides hardware data, software sensors, profile management, aquasuite web and Playground and should therefore always be active.

The hardware monitoring features of the background service can be disabled for specific categories if errors occur. Especially when using hardware monitoring software of different manufacturers at the same time, conflicts can occur when accessing data. Deactivate the hardware monitoring feature of the aquasuite or parts of it in this case.

When maintenance mode is activated, all optional modules of the background service are deactivated. This is useful in case of erroneous settings in the Playground, in particular if a system shutdown is configured and triggers too often. Therefore, in default configuration maintenance mode is automatically enabled if the computer is shut down three times by this feature (recommended setting).

## 19.8. Audio and video



The background service can analyze audio and video data and provide it to connected devices. Both functions can be enabled and disabled separately.

Notices for video analysis: Screen content preventing analysis by DRM or similar methods cannot be analyzed. If a graphics card is configured for variable refresh rate or a modified refresh rate, video analysis may fail; please deactivate this function in the graphics settings of the operating system if necessary.

## 19.9. Updates and update service




For software activation, all aquasuite versions starting with version 2017 require an active update service for the initial release date of the respective version. Update service periods are generally assigned to individual devices, brand-new devices automatically contain update service for a specific period depending on the type of the device. For software activation, at least one device in the computer must contain a corresponding update service period that includes the release date of this software version. If a valid update service period is detected for at least one device, all devices connected to the computer can be used with this version. It is not mandatory that each device has a corresponding update service period. For update service validation, the aquasuite requires an internet connection.

After successful validation, a file containing current data is stored on the computer. A re-validation is performed only if a new software version (update) is installed or upon connection of new devices. New devices can not be used prior to re-validation, even if other devices with corresponding update service periods are connected at the same time.

To purchase update service, please use the “Buy” button, which will open a website with current prices and payment options.

If you have received a key for update service with a device or bought one separately, you may enter the key after clicking the “Register” button. Select a currently

connected USB device from the list for update service assignment. After clicking the “Register key” button, the update service period is permanently assigned to the selected device and stored on the Aqua Computer update server. The key will not have to be re-entered after re-installation of the software or transfer of the device to another computer, but transferring the update service period to another device is not possible.



During update service validation and software activation, device serial numbers and a calculated computer ID are transmitted to and stored on the update server. No further personal information such as IP addresses are stored.

### 19.10. E-mail and MQTT accounts



Accounts for sending e-mail or MQTT messages can be configured. These accounts can then be used to send messages in the “Outputs” section of the Playground.

## 20. Technical details and care instructions

### 20.1. Technical details


Power supply: 5 V DC  $\pm 5\%$ , approx. 50 mA  
 Ambient temperature range: 10 to 40 °C (noncondensing)

### 20.2. Care instructions

Use a dry and soft cloth for cleaning. All electronic components and headers must not get in contact with coolant or water!

### 20.3. Waste disposal

This device has to be disposed of as electronic waste. Please check your local regulations for disposal of electronic waste.



### 20.4. Contact Aqua Computer

We are always happy to answer questions regarding our products and to receive feedback. For answers on frequently asked questions, please also check our website [www.aqua-computer.de](http://www.aqua-computer.de). You might also want to visit our forums and discuss our products with experienced moderators and thousands of members – available 24/7. To get in direct contact with our customer support team, we offer several options:

Email: [support@aqua-computer.de](mailto:support@aqua-computer.de)

Postal address: Aqua Computer GmbH & Co. KG  
Gelliehäuser Str. 1  
37130 Gleichen  
Germany

Tel: +49 (0) 5508 9749290 (9-16 h CET, German and English language)